

## CORROSION-RESISTANT PVC PIPE WRAP TAPE

### TYPICAL APPLICATIONS

- For corrosion protection of under and above ground metal and plastic pipe installations

### PRODUCT FEATURES

- Resists corrosion, moisture, bacteria, fungus and abrasion
- UV-resistant
- Lead free
- Excellent conformability

### CONSTRUCTION

Overall Grade/Function: General Purpose

Backing: 10 mil, PVC film

Adhesive: Non-corrosive, rubber-based

### STANDARD WIDTH(S)

2 in 3 in 4 in 6 in

### STANDARD LENGTH(S)

33.3 yd

Contact your Shurtape sales representative for other available sizes

### STORAGE AND USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

### COLOR(S)



**BLACK PRINTED  
(BPT)**



**BLACK  
(BLK)**

| PHYSICAL PROPERTIES           | STANDARD        | METRIC        |
|-------------------------------|-----------------|---------------|
| Tensile Strength              | 25 lbs/in width | 44.0 N/10 mm  |
| Adhesion to Stainless Steel   | 20 oz/in width  | 2.19 N/10 mm  |
| Thickness                     | 10 mils         | 0.25 mm       |
| Elongation                    | 200%            | 200%          |
| Dielectric Strength           | 600 volts/mil   | 600 volts/mil |
| Application Temperature Range | 14 F to 176 F   | -10 C to 80 C |

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC, Quality Assurance and Technical Service departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

