

# CP 130



## FROGTAPE® PRO GRADE PAINTER'S TAPE



### TYPICAL APPLICATIONS

- For interior or exterior use on cured painted walls and trim, glass and metal

### PRODUCT FEATURES

- Medium adhesion
- Patented PaintBlock® Technology
- Prevents paint bleed to deliver sharp paint lines
- 14-day clean removal
- UV-resistant

### CONSTRUCTION

Overall Grade/Function: Premium  
Backing: Fine structured crepe paper  
Adhesive: Rubber-based

### STANDARD WIDTH(S)

24mm 36mm 48mm

### STANDARD LENGTH(S)

55 m

Contact your Shurtape sales representative for other available sizes

### STORAGE AND USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

### COLOR(S)



### PHYSICAL PROPERTIES

### STANDARD

### METRIC

Tensile Strength	21 lbs/in width	36.78 N/10 mm
Adhesion to Stainless Steel	32 oz/in width	3.50 N/10 mm
Thickness	5.4 mils	0.14 mm
Elongation	10%	10%
Service Temperature Range	50 F to 200 F	10 C to 93 C

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC, Quality Assurance and Technical Service departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.



**Shurtape**  
TECHNOLOGIES