

HW 300

Shurtape®
TRUE TO YOUR WORK™

HOUSEWRAP/SHEATHING TAPE



TYPICAL APPLICATIONS

- For sealing seams on all types of housewrap, sheathing, insulation and vapor barrier materials used in residential and commercial construction applications

PRODUCT FEATURES

- High shear and holding power capabilities
- Can be applied in vast temperature ranges and in humid conditions
- Hand-tearable
- UV-resistant
- First to market water-based (emulsion) acrylic adhesive

CONSTRUCTION

Overall Grade/Function: CCMC Housewrap/Sheathing
Backing: UV-resistant, red/red with black print film
Adhesive: Water-based (emulsion) acrylic

STANDARD WIDTH(S)

60 mm

STANDARD LENGTH(S)

66 m

Contact your Shurtape sales representative for other available sizes

APPLICABLE STANDARDS

CCMC Report No.: 13401-R; FSI 0/SDI 0; Tested in accordance with UL 723

STORAGE AND USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

COLOR(S)



**RED WITH BLACK PRINT
(RPT)**



**RED
(RED)**

PHYSICAL PROPERTIES

STANDARD

METRIC

Tensile Strength	30 lbs/in width	52.5 N/10 mm
Adhesion to Stainless Steel	50 oz/in width	5.47 N/10 mm
Adhesion to Housewrap	26 oz/in width	2.85 N/10 mm
Thickness	3.0 mils	0.07 mm
Elongation	162%	162%
Service Temperature Range	14 F to 176 F	-10 C to 80 C

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC, Quality Assurance and Technical Service departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

